

VR-8x00-SPBU

3.5 inch Touch Screen
DECT handset phone



- Multiple language support.
- Hands-free speakerphone.
- 3.5 inch capacitive touch screen.
- Customizable hotel logo and service dials.
- Two USB charging ports.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> 8 fixed backlit soft touch key: 4 screen feature keys- Home, Dialing, Services, Instructions. 4 functions keys- Speaker, Volume, Language, Message. 	
Display Contents	<ul style="list-style-type: none"> Home page – main logo, power level, DECT signal...etc. Dialing page – 12 dial keys, line status Service Page – 9 speed service dials Instructions – Dialing procedures and instructions. 	
Phone Features	<ul style="list-style-type: none"> Customizable main page Customizable service dials Multiple languages support (up to 5 languages) Handset, Speaker, and Ringer volume control 	<ul style="list-style-type: none"> Hands-free speakerphone Mute and unmute Message waiting
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

2. Hardware Specifications

Handset

Display	<ul style="list-style-type: none"> 3.5" TFT color 320 x 480 capacitive touch screen
Power	<ul style="list-style-type: none"> 3.7v / 900 mAh Li-ion battery Standby Time : 40 hrs Standby Time with keeping Wi-Fi on : 30 hrs Talking Time: 3 hrs
Hard keys	<ul style="list-style-type: none"> Power key x 1
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging
Size and Weight	<ul style="list-style-type: none"> Dimensions:134mm(L) x 61.5mm(W) x 13mm(H), Weight: 145g

Base

Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	<ul style="list-style-type: none"> DC jack x 1, USB type A x 2,
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging
Size and Weight	<ul style="list-style-type: none"> Dimensions:105mm(L) x 91.5mm(W) x 23mm(H) Weight :120g(Base only) Weight :265g(Handset and Base)

3. Regulatory

	USA	EU
RF	FCC Part,15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN62368-1
EMC		EN301489-1/6
		EN301489-17
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

VR-8x08-SPBU

