

# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VR-3100-SBU(S) VR-3200-SBU(S)

3.5 inch Touch Screen Wi-Fi phone











- Multiple language support.
- 3.5 inch capacitive touch screen.
- Customizable hotel logo and service dials.
- Two USB charging ports.
- Optional integration with guestroom management system.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





# **AEi-Corporate Office**

Carrollton, Texas, U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

#### AEI-EMEA Office

London, United Kingdom Sales: +44 (0)1753.643736 emea@aeicommunications.com

#### **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

#### AEi-CEE&CIS Office

Budva, Montenearo Sales: +382 69 891 251 eastern.europe@aeicommunications.com

# **AEi-Corporate Office**

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

Message waiting indicator

Mute and unmute

#### 1. Features

Keys 8 fixed backlit soft touch key:

> 4 screen feature keys- Home, Dialing, Service, Information. 4 functions keys- Volume up/down, Language, Message.

Display Contents Home page – main logo, power level, Wi-Fi signal...etc.

> Dialing page - 12 dial keys, line status Service page – 9 speed service dials

Information page – Dialing procedures or other information.

Phone Features Customizable main page Customizable service dials

Multiple languages support (up to 5 languages)

Handset and Ringer volume control

Integration with GRMS (optional)

Wi-Fi standard 2.4GHz, IEEE 802.11 b/g/n Wi-Fi client

Wi-Fi Encryption WEP, WPA\_PSK, WPA2\_PSK, WPA2\_PSK, WPA2\_ENTERPRISE

Codec G.711 (a-law, µ-law)

Network Protocols DHCP

> SIP SIP V2 (RFC3261)

Security MD5 for SIP authentication (RFC 2069/ RDC2617)

**DTMF** In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)

Tones Ring back tone (local)

# **Hardware Specifications**

# **Handset**

Display 3.5" TFT color 320 x 480 capacitive touch screen

Power 3.7v / 900 mAh Li-ion battery

> Standby Time: 30 hrs Talking Time: 3 hrs

Hard keys Power key x 1

Contact pins 2 contact pins for charging

Size and Weight Dimensions:134mm(L) x 61.5mm(W) x 13mm(H), Weight: 140g

Base

Power AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A

Jacks DC jack x 1, USB type A x 2,

2 contact pins for charging Contact pins

Size and Weight Dimensions:105mm(L) x 91.5mm(W) x 23mm(H)

Weight :120g(Base only) Weight: 260(Handset and Base)

3. Regulatory USA

> **EMI** FCC Part 15B EN300328 FCC Part 15C

Safety EN62368-1 EN301489-1

EN301489-17 **EMC** Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) RoHS

Storage: Low temperature at -10°C Temperature High temperature at +60°C High temperature at +35°C Operating Low temperature at +5°C

Model:

VR-3100-SBU(S) VR-3200-SBU(S)





