

VR-3100-SBU(S)

1- or 2- Line Cordless
 3.5" Touch Screen

VR-3200-SBU(S)

SIP Wi-Fi Phone



VR-3100-SBU(S)

VR-3200-SBU(S)



- Two USB charging ports.
- Multiple language support.
- 3.5-inch capacitive color touch screen.
- Customizable hotel logo and service icons.
- Optional integration with guestroom management system.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> 8 fixed backlit soft touch keys 4 screen feature keys Home - Dialing, Service, Information. 4 functions keys - Volume up/down, Language, Message.
Display Contents	<ul style="list-style-type: none"> Home page – main logo, power level, Wi-Fi signals. Dialing page – 12 dial keys, line status Service page – 9 speed service icons Information page – Dialing procedures or/and hotel information.
Phone Features	<ul style="list-style-type: none"> Customizable main page Multiple languages support (up to 5 languages) Handset and ringer volume control Integration with GRMS (optional) Customizable service icons Message waiting indicator Mute and unmute
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n Wi-Fi client
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK, WPA2_ENTERPRISE
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law)
Network Protocols	<ul style="list-style-type: none"> DHCP
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261)
Security	<ul style="list-style-type: none"> MD5 for SIP authentication (RFC 2069/ RDC2617)
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)
Tones	<ul style="list-style-type: none"> Ring back tone (local)

2. Hardware Specifications

Handset

Display	<ul style="list-style-type: none"> 3.5" TFT color 320 x 480 capacitive touch screen
Power	<ul style="list-style-type: none"> 3.7v / 900mAh Li-ion battery Standby time: 30hrs Talking Time: 3hrs
Hard keys	<ul style="list-style-type: none"> Power key x 1
Contact pins	<ul style="list-style-type: none"> 2 contact pins for charging
Size and Weight	<ul style="list-style-type: none"> Dimensions:134mm(L) x 61.5mm(W) x 13mm(H), Weight: 140g

Base

Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	<ul style="list-style-type: none"> DC jack x 1, USB type A x 2,
Contact pins	<ul style="list-style-type: none"> 3 contact pins
Size and Weight	<ul style="list-style-type: none"> Dimensions:105mm(L) x 91.5mm(W) x 23mm(H) Weight :120g(Base only) Weight :260(Handset and Base)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 300328 EN 62368-1
Safety		EN 301489-1 EN 50360
EMC		EN 301489-17 EN 50566
SAR	FCC 47 CFR § 2.1093	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

VR-3100-SBU(S)

VR-3200-SBU(S)

