

AKD-5100

Single Line Analog  
Emergency Phone



**AKD-5100**

- Desk or wall-mountable.
- Single line analog emergency phone.
- Customizable hotel logo and service dials.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



### 1. Features

- |                                   |  |  |
|-----------------------------------|--|--|
| <p>Keys</p> <p>Phone Features</p> | <ul style="list-style-type: none"> <li>• Function keys</li> <li>• Red color message waiting indicator for ringing and message waiting</li> <li>• Handset volume control</li> </ul> | <p>Volume up/down</p> <ul style="list-style-type: none"> <li>• Ringer volume switch</li> <li>• Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms)</li> </ul> |
|-----------------------------------|--|--|

### 2. Hardware Specifications

- |  |   |
|--|---|
| <p>LED Indications</p> <p>Power</p> <p>Ring Voltage</p> <p>Jacks</p> <p>Line cord</p> <p>Size and Weight</p> | <ul style="list-style-type: none"> <li>• Message waiting indicator</li> <li>• Telephone line powered</li> <li>• 40V RMS minimum</li> <li>• RJ14 PSTN jack x 1, RJ9 Handset jack x 1</li> <li>• 10 feet x 1</li> <li>• Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g</li> </ul> |
|--|---|

### 3. Regulatory

- |             | USA   | EU   |
|-------------|---|--|
| EMC         | FCC Part 15B  | EN 55032 & EN 55035<br>EN 62368-1  |
| RoHS        | <ul style="list-style-type: none"> <li>• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul> |  |
| Telecom     | <ul style="list-style-type: none"> <li>• TIA/EIA 968-B compliant</li> </ul>   |  |
| Temperature | <ul style="list-style-type: none"> <li>• Storage: Low temperature at -10°C</li> <li>• Operating Low temperature at +5°C</li> </ul>        | <ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul> |

**Model:**  
**AKD-5100**

