

AKD-5100

Single Line Analog
Emergency Phone



AKD-5100

- Desk or wall-mountable.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | | |
|----------------|---|--|
| Keys | <ul style="list-style-type: none"> • Function keys • Volume up/down | |
| Phone Features | <ul style="list-style-type: none"> • Desk or wall-mountable • Red color message waiting indicator for ringing and message waiting • Handset volume control | <ul style="list-style-type: none"> • Ringer volume switch • Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms) |

2. Hardware Specifications

- | | |
|-----------------|--|
| LED Indications | <ul style="list-style-type: none"> • Message waiting indicator |
| Power | <ul style="list-style-type: none"> • Telephone line powered |
| Ring Voltage | <ul style="list-style-type: none"> • 40V RMS minimum |
| Jacks | <ul style="list-style-type: none"> • RJ11 PSTN jack x 1, RJ9 Handset jack x 1 |
| Line cord | <ul style="list-style-type: none"> • 6 feet x 1 |
| Size and Weight | <ul style="list-style-type: none"> • Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g |

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN 55032 & EN 55035 EN 62368-1
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> • High temperature at +60°C • High temperature at +35°C

Model:
AKD-5100

