

ALN-5100

Single Line Analog  
Emergency Phone



- Single line analog emergency phone.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





**AEi-Corporate Office**  
 Carrollton, Texas, U.S.A  
 Sales: +1.254.335.0555  
 sales@aeicomcommunications.com

**AEi-EMEA Office**  
 London, United Kingdom  
 Sales: +44 (0)1753.643736  
 emea@aeicomcommunications.com

**AEi-Asia Pacific Office**  
 New Taipei City, Taiwan  
 Sales: +886.2.2696.8809  
 asiapac@aeicomcommunications.com

**AEi-CEE&CIS Office**  
 Budva, Montenegro  
 Sales: +382 69 891 251  
 eastern.europe@aeicomcommunications.com

**AEi-Corporate Office**  
 Penang, Malaysia  
 Sales: +604.3994341  
 so.asia@aeicomcommunications.com

## 1. Features

- |                |   |  |
|----------------|---|--|
| Keys           | • Function keys   | Volume up/down   |
| Phone Features | <ul style="list-style-type: none"> <li>• Red color message waiting indicator for ringing and message waiting</li> <li>• Handset volume control</li> </ul> | <ul style="list-style-type: none"> <li>• Ringer volume switch</li> <li>• Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms)</li> </ul> |

## 2. Hardware Specifications

- |                 |  |
|-----------------|--|
| LED Indications | • Message waiting indicator                              |
| Power           | • Telephone line powered                                 |
| Ring Voltage    | • 40V RMS minimum  |
| Jacks           | • RJ14 PSTN jack x 1 ,RJ9 Handset jack x1                |
| Line cord       | • 10 feet x 1  |
| Size and Weight | • Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	<ul style="list-style-type: none"> <li>• Storage: Low temperature at -10°C</li> <li>• Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

**Model:**  
**ALN-5100**

