

SFT-1100

Single Line  
SIP Phone



- Single line SIP wall mount phone.
- Magnetic hook switch.
- Faceplate with customizable hotel logo.
- Coiled cord.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Phone Features	<ul style="list-style-type: none"> <li>Red color ring indicator</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP</li> <li>Phone remote resetting</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> <li>SIP V2 (RFC3261)</li> </ul>
SIP Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>
	<ul style="list-style-type: none"> <li>Firmware upgrade via TFTP</li> <li>Phone status monitoring system</li> </ul>
	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Ring indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE : IEEE 802.3af compliant</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>0.5 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 455g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN 60950-1
EMC		EN55024
		EN61000-3-2
		EN61000-3-3
		IEC61000-4-2
		IEC61000-4-3
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

### Model:

SFT-1100

SFT-1100-BC

