

SKD-1110	1- or 2- Line SIP Phone
SKD-1210	



SKD-1110



SKD-1210

- Desk or wall-mountable.
- Message waiting indicator.
- Faceplate with customizable hotel logo.
- Up to 10 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	1110	1210
Dialing keys	(0~9, *, #)	(0~9, *, #)
Line keys	N/A	Line1, Line2
Function keys	HOLD, REDIAL, Volume up/down, 10 guest service keys	
Phone Features	- Up to 10 programmable guest service keys - Desk or wall-mountable - Red color message waiting indicator for ringing and message waiting	- Handset and ringer volume control - Redial last call - Call hold and resume
Easy Administration	- Web GUI. - Auto provisioning	Firmware upgrade via web.
Codec	G.711 (a-law, μ-law)	
Network Protocol	- HTTP server - ToS / VLAN IEEE 802.1 p/q	Static IP, DHCP Client
SIP	SIP V2 (RFC3261)	
Security	- Web login authentication for web setup - MD5 for SIP authentication (RFC2069/ RFC2617)	TLS 1.2
DTMF	In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality	- CNG: comfortable noise generator - Echo canceller: LEC / AEC - Jitter buffer/PLC	
Tones	Ring back tone (local), Busy tone, Dial tone	

2. Hardware Specifications

LED Indications	Line keys (1210), message waiting indicator
Power	- PoE: IEEE 802.3af compliant - AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	RJ45 10/100Mbps: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	6 feet x 1
Size and Weight	Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Model:

SKD-1110

SKD-1210

