

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

> AGR-6106-S Single line AGR-6109-S

- Single line analog phone.
- Hearing aid support
- Full duplex speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office Carrollton, Texas, U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

AEi-EMEA Office London, United Kingdom Sales: +44 (0)1753.643736 emea@aeicommunications.com **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com AEi-Corporate Office Penang, Malaysia Sales: +604.3994341

so.asia@aeicommunications.com

| Keys | Dial keys | (0~9, *, #) | | | | | |
|----------------|---|-------------------------|--|-----------------|--|-------------------------|-----------------------|
| | Line keys | N/A | | | | | |
| | Function keys | Speaker, Volume up/o | down, 6 or 9 programmable service keys | | | | |
| Phone Features | Single line telephone system with speakerphone | | | | | | |
| | Adjustable High-low ringer (2 way selectable switch) 8 steps speakerphone digital volume control 4 steps handset digital volume control 6 non volatile one-touch programmable speed dial memory button Tone dialing only Hearing Aid Receiver Compliant PBX / Standard Line compatible Multi Purpose LED indicator for Message Waiting and Incoming Ring | | | | | | |
| | | | | | | | |
| | | | | . Hardware Spec | | | |
| | | | | Power | Line Power (without AC adaptor or battery) | | |
| | | | | Ring Voltage | 40V RMS minimum | | |
| | | | | | Jacks • RJ11 PSTN jack x 1 | | |
| | | | | Size and Weight | • Dimensions: 19 | 91mm(L) x 110mm(W) x 10 | 06mm(H), Weight: 576g |
| | | | | . Regulatory | | USA | EU |
| PSTN | FCC Part 68 | | | | | | |
| EMI | FCC | Part 15B | EN55032 & EN55024 | | | | |
| | | | EN60950-1 | | | | |
| RoHS • | Comply with direct | ive 2002/95/EC RoHS (as | amended by commission decision 2005/613/EC | | | | |
| Telecom | TIA/EIA 968-B con | | | | | | |
| Temperature • | | mperature at -10°C | High temperature at +60°C | | | | |
| | Operating Low te | | High temperature at +35°C | | | | |
| | Operating LOW le | | | | | | |
| | | | | | | | |
| | | | | | | | |

Model: AGR-6106-S AGR-6109-S

FC CE **RoHS** compliant

Specifications are subject to change without notice. Design Patent Pending©2018 AEI Communications. All rights reserved.