

AGR-6106-S

Single line

AGR-6109-S

Analog phone



- Hearing aid support.
- Handsfree speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys N/A • Function keys Speaker, Volume up/down, 6 or 9 programmable service keys |
| Phone Features | <ul style="list-style-type: none"> • Single line telephone system with speakerphone • Adjustable High-low ringer (2-way selectable switch) • 8 steps speakerphone digital volume control • 4 steps handset digital volume control • 6 or 9 one-touch programmable speed dial memory buttons • Tone dialing only • Hearing Aid Receiver Compliant • PBX / Standard Line compatible • Multi Purpose LED indicator for Message Waiting and Incoming Ring |

2. Hardware Specifications

- | | |
|-----------------|--|
| Power | • Line Power (without AC adaptor or battery) |
| Ring Voltage | • 40V RMS minimum |
| Jacks | • RJ11 PSTN jack x 1 |
| Size and Weight | • Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g |

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

AGR-6106-S

AGR-6109-S

