

AGR-8106-SMK (Non-display)

Single Line
Cordless Analog
Phone



- Single line cordless analog phone.
- Dual keypads dialing.
- Full duplex speakerphone.
- Message waiting indicator.
- Pair up to 4 cordless remotes.
- 6 customizable service dials.
- Faceplate with customizable hotel logo.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Handset

Keys	<ul style="list-style-type: none"> ● Dial keys (0~9, *, #) ● Line keys Line, END ● Function keys Mute, Speaker, Volume, 6 Service dial keys
Phone Features	<ul style="list-style-type: none"> ● Single Line ● Handset, Speaker, and Ringer volume control ● Red color message waiting indicator for ringing and message waiting ● 6 programmable service dials ● Mute and unmute ● Full duplex speaker phone
DECT Standard	<ul style="list-style-type: none"> ● DECT / CAT iq 2.0 compatible ● Radio Frequency Range : 1880~1930 MHz ● EU : 1881.792(ch0)~1897.344(ch9) 10 Channels ● US : 1921.536(ch0)~1928.448(ch4) 5 Channels ● JP : 1895.616(ch0)~1902.528(ch4) 5 Channels ● Channel Space : 1728 KHz ● Bit rate : 1150 Kbit/s ● Modulation : GFSK ● Voice coding : 16 Kbit/s ● RF power : 7 dBm

Base

Keys	<ul style="list-style-type: none"> ● Dial keys (0~9, *, #) ● Line keys Line, END ● Function keys Mute, Speaker, Volume, 6 Service dial keys
Phone Features	<ul style="list-style-type: none"> ● Single Line ● Speaker, and Ringer volume control ● Red color message waiting indicator for ringing and message waiting ● 6 programmable service dials ● Mute and unmute ● Full duplex speaker phone
DECT Standard	<ul style="list-style-type: none"> ● DECT / CAT iq2.0 compatible ● Radio Frequency Range : 1880~1930 MHz ● EU : 1881.792(ch0)~1897.344(ch9) 10 Channels ● US : 1921.536(ch0)~1928.448(ch4) 5 Channels ● JP : 1895.616(ch0)~1902.528(ch4) 5 Channels ● Channel Space : 1728 KHz ● Bit rate : 1150 Kbit/s ● Modulation : GFSK ● Voice coding : 16 Kbit/s ● RF power : 17 dBm

2. Hardware Specifications

Handset

- LED Indications
 - Message waiting indicator and keypad backlight
- Power
 - 3.7v / 900 mAh Li-ion battery
 - Charging Time : 5 hrs
 - Standby Time : 240 hrs
 - Talking Time: 9 hrs
- Contact pins
 - 3 contact pins for charging, hook detecting and auto-pairing
- Size and Weight
 - Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)

Base

- LED Indications
 - Line, Mute, Speaker keys, Message waiting, and Handset charging indicators
- Power
 - AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
- Jacks
 - RJ14 PSTN jack x 1, DC jack x 1
- Contact pins
 - 3 contact pins for charging, hook detecting and auto-pairing
- Line cord
 - 10 feet x 1
- Size and Weight
 - Dimensions:193mm(L) x109mm(W) x 102mm(H), Weight: 430g
 - Dimensions:193mm(L) x109mm(W) x 111mm(H), Weight: 610g (handset included)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/-6
PSTN	Part 68	TBR21
RoHS	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

AGR-8106-SMK-7979 (Non-display)

