

AGR-8106-SMK Non-display

Single Line Cordless
Analog DECT Master Phone



AGR-8106-SMK Non-display

- Dual keypad dialing.
- Magnetic hook switch.
- Message waiting indicator.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Faceplate with customizable hotel logo.
- Up to 6 customizable guest service keys.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Handset

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line, END • Function keys MUTE, SPEAKER, VOLUME, 6 guest service keys |
| Phone Features | <ul style="list-style-type: none"> • Up to 6 programmable guest service keys • Handset, speaker, and ringer volume control • Red color message waiting indicator for ringing and message waiting • Full duplex speaker phone • Mute and unmute |
| DECT Standard | <ul style="list-style-type: none"> • DECT / CAT iq 2.0 compatible • Radio Frequency Range : 1880~1930 MHz • EU : 1881.792(ch0)~1897.344(ch9) 10 channels • US : 1921.536(ch0)~1928.448(ch4) 5 channels • JP : 1895.616(ch0)~1902.528(ch4) 5 channels • Channel Space : 1728 KHz • Bit rate : 1150 Kbit/s • Modulation : GFSK • Voice coding : 16 Kbit/s • RF power : 7 dBm |

Base

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line, END • Function keys MUTE, SPEAKER, VOLUME, 6 guest service keys |
| Phone Features | <ul style="list-style-type: none"> • Up to 6 programmable guest service keys • Red color message waiting indicator for ringing and message waiting • Full duplex speaker phone • Mute and unmute • Speaker and ringer volume control |
| DECT Standard | <ul style="list-style-type: none"> • DECT / CAT iq2.0 compatible • Radio Frequency Range : 1880~1930 MHz • EU : 1881.792(ch0)~1897.344(ch9) 10 channels • US : 1921.536(ch0)~1928.448(ch4) 5 channels • JP : 1895.616(ch0)~1902.528(ch4) 5 channels • Channel Space : 1728 KHz • Bit rate : 1150 Kbit/s • Modulation : GFSK • Voice coding : 16 Kbit/s • RF power : 17 dBm |

2. Hardware Specifications

Handset

- | | | |
|-----------------|--|------------------------|
| LED Indications | • Message waiting indicator and keypad backlight | |
| Power | • 3.7v / 900mAh Li-ion battery | • Standby time: 240hrs |
| | • Charging time: 5hrs | • Talking time: 9hrs |
| Contact pins | • 3 contact pins for charging, hook detecting and auto-pairing | |
| Size and Weight | • Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included) | |

Base

- | | | |
|-----------------|---|--|
| LED Indications | • Line keys, MUTE, SPEAKER keys, message waiting, and handset charging indicators | |
| Power | • AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A | |
| Jacks | • RJ14 PSTN jack x 1, DC jack x 1 | |
| Contact pins | • 3 contact pins for charging, hook detecting and auto-pairing | |
| Line cord | • 6 feet x 1 | |
| Size and Weight | • Dimensions:193mm(L) x109mm(W) x 102mm(H), Weight: 430g | |
| | • Dimensions:193mm(L) x109mm(W) x 111mm(H), Weight: 610g (handset included) | |

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

AGR-8106-SMK-7979 non-display

