

GR-8106-SPB Non-display

Single Line Cordless
Handset Phone



GR-8106-SPB Non-display

- Customizable hotel logo.
- Full duplex speakerphone.
- Message waiting indicator.
- Up to 6 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

Keys	- Dial keys (0~9, *, #) - Line keys Line, END - Function keys MUTE, SPEAKER, VOLUME - Service keys Up to 6	
Phone Features	- Up to 6 programmable guest service dial keys - Mute and unmute - Handset, Speaker, and Ringer volume control	- Full duplex speaker phone - Red color message waiting indicator for ringing and message waiting
DECT Standard	- DECT / CAT iq2.0 compatible - Radio Frequency Range : 1880~1930 MHz - EU : 1881.792(ch0)~1897.344(ch9) 10 Channels - US : 1921.536(ch0)~1928.448(ch4) 5 Channels - JP : 1895.616(ch0)~1902.528(ch4) 5 Channels	- Channel Space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 7 dBm

2. Hardware Specifications

Handset

LED Indications	Message waiting indicator and keypad backlight	
Power	3.7v / 900mAh Li-ion battery - Charging Time: 5hrs	- Standby Time: 240hrs - Talking Time: 9hrs
Contact pins	3 contact pins for charging and hook detecting	
Size and Weight	Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)	

Stand Cradle

LED Indications	Handset charging indicators
Power	AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	DC jack x 1
Contact pins	3 contact pins for charging and hook detecting
Size and Weight	- Dimensions: 106mm(L) x 88mm(W) x 97mm(H), Weight: 290g - Dimensions: 106mm(L) x 88mm(W) x 179mm(H), Weight: 455g (handset included)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60368-1
EMC		EN 301489-1/6
RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Model:

GR-8106-SPB Non-display

