

GR-8106-SPBU
(Non-display)

Single Line Cordless
Handset phone



- Full duplex speakerphone.
- Single USB charging port.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

- | | |
|----------------|---|
| Keys | <ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line, END Function keys Mute, Speaker, Volume, 6 Service dial keys |
| Phone Features | <ul style="list-style-type: none"> Handset, Speaker, and Ringer volume control USB power jack for mobile device charging Red color message waiting indicator for ringing and message waiting 6 programmable service dials Mute and unmute Full duplex speaker phone |
| DECT Standard | <ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm |

2. Hardware Specifications

Handset

- | | |
|-----------------|---|
| LED Indications | <ul style="list-style-type: none"> Message waiting indicator and keypad backlight |
| Power | <ul style="list-style-type: none"> 3.7v / 900 mAh Li-ion battery Charging Time : 5 hrs Standby Time : 240 hrs Talking Time: 9 hrs |
| Contact pins | <ul style="list-style-type: none"> 3 contact pins for charging and hook detecting |
| Size and Weight | <ul style="list-style-type: none"> Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included) |

Stand Cradle

- | | |
|-----------------|--|
| LED Indications | <ul style="list-style-type: none"> Handset charging indicators |
| Power | <ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A |
| Jacks | <ul style="list-style-type: none"> DC jack x 1, USB type A x 1 |
| Contact pins | <ul style="list-style-type: none"> 3 contact pins for charging and hook detecting |
| Size and Weight | <ul style="list-style-type: none"> Dimensions:106mm(L) x88mm(W) x 97mm(H), Weight: 290g Dimensions:106mm(L) x88mm(W) x 179mm(H), Weight: 455g (handset included) |

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

GR-8106-SPBU (Non-display)

