

SGR-9106-S

1- or 2- Line Coded
SIP Phone

SGR-9206-S



SGR-9106-S



SGR-9206-S

- Full duplex speakerphone.
- Message waiting indicator.
- Faceplate with customizable hotel logo.
- Up to 6 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	9206	9106
		<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2 with LED, End • Function keys SPEAKER, HOLD, VOLUME, 6 guest service keys 	<ul style="list-style-type: none"> • (0~9, *, #) • Line with LED, End • SPEAKER, MUTE, VOLUME, 6 guest service keys
	Phone Features	<ul style="list-style-type: none"> • Call hold and resume (9206 only) • Up to 6 programmable guest service keys • Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> • Mute and unmute (9106 only) • Hands-free speaker phone • Handset, speaker and ringer volume control
	Easy Administration	<ul style="list-style-type: none"> • Web GUI • Auto provisioning via TFTP 	<ul style="list-style-type: none"> • Firmware upgrade via TFTP
	Codec	<ul style="list-style-type: none"> • G.711 (a-law, μ-law) 	
	Network Protocol	<ul style="list-style-type: none"> • HTTP server • ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> • Static IP, DHCP Client
	SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261) 	
	Security	<ul style="list-style-type: none"> • Web login authentication for web setup • MD5 for SIP authentication (RFC 2069/ RFC2617) • TLS 1.2 	
	DTMF	<ul style="list-style-type: none"> • In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
	Voice Quality	<ul style="list-style-type: none"> • CNG: comfortable noise generator • Echo canceller: LEC / AEC • Jitter buffer/PLC 	
	Tones	<ul style="list-style-type: none"> • Ring back tone (local), Busy tone, Dial tone 	

2. Hardware Specifications

- LED Indications
 - Line keys(white), HOLD/MUTE key(red), SPEAKER key(red), and message waiting indicator(red)
- Power
 - PoE: IEEE 802.3af compliant
 - AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
- Jacks
 - RJ45 10/100Mbps: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
- Ethernet cable
 - 9 feet x 1
- Size and Weight
 - Dimensions:193mm(L) x109mm(W) x 105mm(H), Weight: 595g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

SGR-9106-S-99

SGR-9206-S-99

SGR-9106-S-9901

SGR-9206-S-9901

