


VM-8108-SMK-NL(S)

1 or 2 Lines
 Cordless SIP
 Phone

VM-8208-SMK-NL(S)



- 1 or 2 lines cordless phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	Keys	8208	8108
	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2, END • Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys 	<ul style="list-style-type: none"> • (0~9, *, #) • Line, END • SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys 	
Phone Features	<ul style="list-style-type: none"> • One or Two Lines • 3 hard key and 7 scrollable service dials • Call Hold and resume(8208 only) • Handset, Speaker, and Ringer volume control 	<ul style="list-style-type: none"> • Full duplex speaker phone • Mute and unmute(8108 only) • Red color message waiting indicator for ringing and message waiting 	
Display Contents	<ul style="list-style-type: none"> • Main logo • Service dial list/icons • Battery status: power level, charging status 	<ul style="list-style-type: none"> • DECT signal status • Line status • Firmware Version 	
DECT Standard	<ul style="list-style-type: none"> • DECT / CAT iq2.0 compatible • Radio frequency range : 1880~1930 MHz • EU : 1881.792(ch0)~1897.344(ch9) 10 channels • US : 1921.536(ch0)~1928.448(ch4) 5 channels • JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> • Channel space : 1728 KHz • Bit rate : 1150 Kbit/s • Modulation : GFSK • Voice coding : 16 Kbit/s • RF power : 7 dBm 	

Base

	8208	8108
Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2 with red color LED • Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys 	<ul style="list-style-type: none"> • (0~9, *, #) • N/A • REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys
Phone Features	<ul style="list-style-type: none"> • 8 customizable service dials • Call Hold and resume(8208 only) • Handset, speaker and ringer volume control • Red color message key with indicator 	<ul style="list-style-type: none"> • Full duplex speaker phone • Mute and unmute(8108 only) • Redial last call • Ringing indicator
Easy Administration	<ul style="list-style-type: none"> • Web GUI • Auto provisioning via TFTP 	<ul style="list-style-type: none"> • Firmware upgrade via TFTP
Codec	<ul style="list-style-type: none"> • G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> • HTTP server • ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> • Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> • Web login authentication for web setup • MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> • HTTPS • TLS 1.2
DTMF	<ul style="list-style-type: none"> • In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> • Echo canceller: LEC / AEC • CNG: Comfortable noise generator 	<ul style="list-style-type: none"> • Jitter buffer/PLC
Tones	<ul style="list-style-type: none"> • Ring back tone (local), Busy tone, Dial tone 	
DECT Standard	<ul style="list-style-type: none"> • DECT / CAT iq2.0 compatible • Radio Frequency Range : 1880~1930 MHz • EU: 1881.792(ch0)~1897.344(ch9) 10 channels • US: 1921.536(ch0)~1928.448(ch4) 5 channels • JP: 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> • Channel Space : 1728 KHz • Bit rate : 1150 Kbit/s • Modulation : GFSK • Voice coding : 16 Kbit/s • RF power : 17 dBm

2. Hardware Specifications

Handset

- Display • 2.0" TFT color display
- LED Indications • Message waiting indicator and keypad backlight
- Power • 3.7v / 900 mAh Li-ion battery • Standby Time : 240 hrs
- Charging Time : 5 hrs • Talking Time: 9 hrs
- Contact pins • 3 contact pins for charging, hook detecting and auto-pairing
- Size and Weight • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

- LED Indications • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
- Power • PoE : IEEE 802.3af compliant
- AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
- Jacks • RJ45 10/100 Mbs: LAN port x 1; DC jack x 1
- Contact pins • 3 contact pins for charging and hook detecting.
- Ethernet cable • 9 feet x 1
- Size and Weight • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 540g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

Model:

- VM-8108-SMK-NL-997901(S)
- VM-8208-SMK-NL-997901(S)
- VM-8108-SMK-NL-997901TI(S)
- VM-8208-SMK-NL-997901TI(S)

