


VM-8108-SMK(A)

VM-8208-SMK(A)

1- or 2- Line Cordless
Analog DECT Master Phone



VM-8108-SMK(A)



VM-8208-SMK(A)

- Magnetic hook switch.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	8208	8108
Keys	- Dial keys (0~9, *, #) - Line keys Line1, Line2, END - Hard keys EMERGENCY, GUEST SERVICES, MESSAGE - Function keys Info, VOLUME +/-, HOLD, and 3 soft keys	(0~9, *, #) - Line, END - EMERGENCY, GUEST SERVICES, MESSAGE - Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features	- Up to 7 on-screen scrolling guest service icons - Call hold and resume (8208) - Full duplex speaker phone - Handset, speaker, and ringer volume control	3 programmable hard keys - Mute and unmute (8108) - Red color message waiting indicator for ringing and message waiting
Display Contents	- Main logo - Service dial list/icons - Battery status: power level, charging status	- DECT signal status - Line status - Firmware version
DECT Standard	- DECT / CAT iq2.0 compatible - Radio frequency range : 1880~1930 MHz - EU: 1881.792(ch0)~1897.344(ch9) 10 channels - US: 1921.536(ch0)~1928.448(ch4) 5 channels - JP: 1895.616(ch0)~1902.528(ch4) 5 channels	- Channel space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 7 dBm

Base

	8208	8108
Keys	- Dial keys (0~9, *, #) - Line keys Line1, Line2 with red color LED - Function keys REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys	(0~9, *, #) - N/A - REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	- Up to 8 programmable guest service keys - Programmable voice message key with indicator - Call hold and resume(8208) - Speaker and ringer volume control	- Redial last call - Ringing indicator - Mute and unmute(8108) - Full duplex speaker phone
DECT Standard	- DECT / CAT iq2.0 compatible - Radio frequency range : 1880~1930 MHz - EU: 1881.792(ch0)~1897.344(ch9) 10 channels - US: 1921.536(ch0)~1928.448(ch4) 5 channels - JP: 1895.616(ch0)~1902.528(ch4) 5 channels	- Channel space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 17 dBm

2. Hardware Specifications

Handset

- | | | |
|-----------------|--|------------------------|
| Display | • 2.0" TFT color display | |
| LED Indications | • Message waiting indicator and keypad backlight | |
| Power | • 3.7v / 900mAh Li-ion battery | • Standby time: 240hrs |
| | • Charging time: 5hrs | • Talking time: 9hrs |
| Contact pins | • 3 contact pins for charging, hook detecting and auto-pairing | |
| Size and Weight | • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included) | |

Base

- | | |
|-----------------|--|
| LED Indications | • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys |
| Power | • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A |
| Jacks | • RJ14(RJ11) PSTN jack x 1, DC jack x 1 |
| Contact pins | • 3 contact pins for charging and hook detecting. |
| Line cord | • 6 feet x 1 |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 510g |

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 62368-1
EMC		EN 301489-1/-6
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Model:

VM-8108-SMK(A)

VM-8208-SMK(A)

