

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

BY-3000-X(A)

Analog BYOD Master



- Analog BYOD Master.
- Extended analog telephony system to Wi-Fi
- Compact size mounted under table or cabinet\
- Connects with 2 smart phones and 2 AEI Wi-Fi phones.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas , U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

AEI-EMEA Office

London, United Kingdom Sales: +44 (0)1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Phone Features

Links with 2 private mobile phones and 2 Wi-Fi extension phones

Connected to existing analog phone

Wi-Fi standard

2.4GHz, IEEE 802.11 b/g/n

Wi-Fi Encryption

WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK

Easy Administration • Firmware upgrade via Wi-Fi

2. Hardware Specifications

LED Indications

Wi-Fi link indicator

Power

AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A

Jacks

RJ11 PSTN jack x 2, DC jack x 1, Reset x 1

Line cable

10 feet x 1

Size and Weight

Dimensions: 113mm(L) x113mm(W) x 36mm(H), Weight:350g

3.	Regulatory	USA	EU	
	EMI	FCC Part 15B	EN55032	EN55024
		FCC Part 15C	EN300328	
	Safety		EN 62386-1	
	EMC		EN301489-1	EN301489-17
	SAR	FCC 47 CFR § 2.1093	EN50360	EN50566
	RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
	Temperature	Storage: Low temperature at -10°C	High temperature at +60°C	
		 Operating Low temperature at +5°C 	High temperature at +35°C	

Model: BY-3000-X(A)



