

BY-3000-X(A)

Analog BYOD Master



- Analog BYOD Master.
- Extended analog telephony system to Wi-Fi
- Compact size – mounted under table or cabinet
- Connects with 2 smart phones and 2 AEI Wi-Fi phones.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

- | | |
|---------------------|--|
| Phone Features | <ul style="list-style-type: none"> • Links with 2 private mobile phones and 2 AEI Wi-Fi phones. • Connected to existing analog phone |
| Wi-Fi standard | <ul style="list-style-type: none"> • 2.4GHz, IEEE 802.11 b/g/n |
| Wi-Fi Encryption | <ul style="list-style-type: none"> • WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK |
| Easy Administration | <ul style="list-style-type: none"> • Firmware upgrade via Wi-Fi |

2. Hardware Specifications

- | | |
|-----------------|---|
| LED Indications | <ul style="list-style-type: none"> • Wi-Fi link indicator |
| Power | <ul style="list-style-type: none"> • AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A |
| Jacks | <ul style="list-style-type: none"> • RJ11 PSTN jack x 2, DC jack x 1, Reset x 1 |
| Line cable | <ul style="list-style-type: none"> • 6 feet x 1 |
| Size and Weight | <ul style="list-style-type: none"> • Dimensions: 113mm(L) x113mm(W) x 36mm(H), Weight:350g |

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 55032 EN 300328
Safety		EN 62386-1
EMC		EN 301489-1
SAR	FCC 47 CFR § 2.1093	EN 50360
PSTN	TIA/EIA 968-B compliant	EN 50566
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:
BY-3000-X(A)

