

VX-3108-B(S)

VX-3208-B(S)

1- or 2- Line Cordless
Wi-Fi Phone



VX-3108-B(S)



VX-3208-B(S)

- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	3208	3108
		- Dial keys (0~9, *, #) - Line keys Line1, Line2, END - Hard keys EMERGENCY, GUEST SERVICES, MESSAGE - Function keys Info, VOLUME +/-, HOLD, and 3 soft keys	(0~9, *, #) - Line, END - EMERGENCY, GUEST SERVICES, MESSAGE - Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features		- Up to 7 on-screen scrolling guest service icons - Call hold and resume (3208) - Red color message waiting indicator for ringing and message waiting	3 programmable hard keys - Mute and unmute (3108) - Handset and ringer volume control
Display Contents		- Main logo - Battery status, charging status - Customizable vivid color display scheme - Service dial list/icons	- Firmware version - Line status - Wi-Fi signal
Easy Administration		Firmware upgrade via Wi-Fi	Provisioning via Wi-Fi
Codec		G.711 (a-law, μ-law)	
Network Protocols		DHCP	
SIP		SIP V2 (RFC3261)	
Security		MD5 for SIP authentication (RFC 2069/ RDC2617)	
DTMF		In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Tones		Ring back tone (local)	
Wi-Fi standard		2.4GHz, IEEE 802.11 b/g/n	
Wi-Fi Encryption		WEP, WPA PSK, WPA2 PSK, WPA WPA2 PSK	

2. Hardware Specifications

Handset	
Display	2.0" TFT color display
LED Indications	Message waiting indicator and keypad backlight
Power	3.7v / 900mAh Li-ion battery - Standby time: 30hrs - Talking time: 200mins
Contact pins	3 contact pins for charging
Size and Weight	Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)
Base	
Power	AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	DC jack x 1
Contact pins	3 contact pins for charging
Size and Weight	- Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g - Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 300328 EN 62368-1
Safety		EN 301489-1
EMC		EN 50360
SAR	FCC 47 CFR § 2.1093	EN 301489-17 EN 50566
RoHS	Comply with directive 2011/65/EU	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Models:

VX-3108-B(S)

VX-3208-B(S)

