

VX-3108-B(S)

VX-3208-B(S)

DCS 1- or 2- Line
Cordless Wi-Fi Phone



VX-3108-B(S)



VX-3208-B(S)

- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	3208	3108
	- Dial keys - Line keys - Hard keys - Function keys	(0~9, *, #) Line1, Line2, END EMERGENCY, GUEST SERVICES, MESSAGE Info, VOLUME +/-, HOLD, and 3 soft keys	(0~9, *, #) Line, END EMERGENCY, GUEST SERVICES, MESSAGE Info, VOLUME +/-, MUTE, and 3 soft keys
Display Contents	- Up to 7 on-screen scrolling guest service icons - Call hold and resume (3208) - Red color message waiting indicator for ringing and message waiting		3 programmable hard keys - Mute and unmute (3108) - Handset and ringer volume control
* To activate voice messaging within DCS, DCS DESKTOP software is required and available for purchase separately.			
Phone Features	- Main logo - Battery status, charging status - Customizable vivid color display scheme - Service dial list/icons		- Firmware version - Line status - Wi-Fi signal
Easy Administration	Firmware upgrade via Wi-Fi		Provisioning via Wi-Fi
Codec	G.711 (a-law, μ-law)		
Network Protocols	DHCP		
SIP	SIP V2 (RFC3261)		
Security	MD5 for SIP authentication (RFC 2069/ RDC2617)		
DTMF	In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)		
Tones	Ring back tone (local)		
Wi-Fi standard	2.4GHz, IEEE 802.11 b/g/n		
Wi-Fi Encryption	WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK		

2. Hardware Specifications

Handset	
Display	2.0" TFT color display
LED Indications	Message waiting indicator and keypad backlight
Power	3.7v / 900mAh Li-ion battery - Standby time: 30hrs - Talking time: 200mins
Contact pins	3 contact pins for charging
Size and Weight	Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)
Base	
Power	AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	DC jack x 1
Contact pins	3 contact pins for charging
Size and Weight	- Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g - Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN300328 EN62368-1
Safety		EN301489-1 EN50360
EMC		EN301489-17 EN50566
SAR	FCC 47 CFR § 2.1093	
RoHS	Comply with directive 2011/65/EU	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	High temperature at +60°C High temperature at +35°C
Models:		
VX-3108-B(S)		
VX-3208-B(S)		

