AEi COMMUNICATIONS

Serving the Hospitality Industry with Advanced **IP and Analog** Telephony Solutions **Worldwide**

VX-3108-B(S)
VX-3208-B(S)

DCS 1- or 2- Line Cordless Wi-Fi Phone



VX-3108-B(S)



VX-3208-B(S)

- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.

www.aeicommunication.com

AEI COMMUNICATIONS

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

1. Features

		3208	3108
Keys	• Dial keys	(0~9, *, #)	(0~9, *, #)
	• Line keys	Line1, Line2, END	Line, END
	• Hard keys	EMERGENCY, GUEST SERVICES, MESSAGE	EMERGENCY, GUEST SERVICES, MESSAGE
	• Function keys	Info, VOLUME +/-, HOLD, and 3 soft keys	Info, VOLUME +/-, MUTE, and 3 soft keys
Display Contents	• Up to 7 on-screen scrolling guest service icons • Call hold and resume (3208) • Red color message waiting indicator for ringing and message waiting		• 3 programmable hard keys • Mute and unmute (3108) • Handset and ringer volume control

** To activate voice messaging within DCS, **DCS DESKTOP** software is required and available for purchase separately.*

Phone Features	• Main logo • Battery status, charging status • Customizable vivid color display scheme • Service dial list/icons	• Firmware version • Line status • Wi-Fi signal
Easy Administration	• Firmware upgrade via Wi-Fi	• Provisioning via Wi-Fi
Codec	• G.711 (a-law, μ-law)	
Network Protocols	• DHCP	
SIP	• SIP V2 (RFC3261)	
Security	• MD5 for SIP authentication (RFC 2069/ RDC2617)	
DTMF	• In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Tones	• Ring back tone (local)	
Wi-Fi standard	• 2.4GHz, IEEE 802.11 b/g/n	
Wi-Fi Encryption	• WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK	

2. Hardware Specifications

Handset

Display	• 2.0“ TFT color display
LED Indications	• Message waiting indicator
Power	• 3.7v / 900mAh Li-ion battery • Standby time: 30hrs • Talking time: 200mins
Contact pins	• 3 contact pins for charging
Size and Weight	• Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)

Base

Power	• AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	• DC jack x 1
Contact pins	• 3 contact pins for charging
Size and Weight	• Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g • Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included)

3. Regulatory

	USA	EU	
EMI	FCC Part 15B FCC Part 15C	EN300328	
Safety		EN62368-1	
EMC		EN301489-1	EN301489-17
SAR	FCC 47 CFR § 2.1093	EN50360	EN50566
RoHS	Comply with directive 2011/65/EU		
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C	
	• Operating: Low temperature at +5°C	High temperature at +35°C	

Models:

VX-3108-B(S)

VX-3208-B(S)

Specifications are subject to change without notice.
Design Patent Pending©2018 AEI Communications. All rights reserved.