

VX-3108-BU(S)

1- or 2-Lines Cordless  
Wi-Fi Phone

VX-3208-BU(S)



**VX-3108-BU(S)**



**VX-3208-BU(S)**

- Two USB charging ports.
- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- 3 hard keys and 7 scrollable service dials.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



### 1. Features

	Keys	3208	3108
	<ul style="list-style-type: none"> <li>Dial keys</li> <li>Line keys</li> <li>Function keys</li> </ul>	(0~9, *, #) Line1, Line2, END Info, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys	(0~9, *, #) Line, END Info, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
Display Contents	<ul style="list-style-type: none"> <li>Main logo</li> <li>Battery status, charging status</li> <li>Customizable vivid color display scheme</li> <li>Service dial list/icons</li> </ul>		<ul style="list-style-type: none"> <li>Firmware Version</li> <li>Line status</li> <li>Wi-Fi signal</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>3 hard key and 7 scrollable service dials</li> <li>Call Hold and resume (3208 only)</li> <li>Handset and Ringer volume control</li> </ul>		<ul style="list-style-type: none"> <li>Mute and unmute (3108 only)</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Firmware upgrade via Wi-Fi</li> </ul>		<ul style="list-style-type: none"> <li>Provisioning via Wi-Fi</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>		
Network Protocols	<ul style="list-style-type: none"> <li>DHCP</li> </ul>		
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>		
Security	<ul style="list-style-type: none"> <li>MD5 for SIP authentication (RFC 2069/ RDC2617)</li> </ul>		
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>		
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local)</li> </ul>		
Wi-Fi standard	<ul style="list-style-type: none"> <li>2.4GHz, IEEE 802.11 b/g/n</li> </ul>		
Wi-Fi Encryption	<ul style="list-style-type: none"> <li>WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK</li> </ul>		

### 2. Hardware Specifications

Handset	
Display	<ul style="list-style-type: none"> <li>2.0" TFT color display</li> </ul>
LED Indications	<ul style="list-style-type: none"> <li>Message waiting indicator and keypad backlight</li> </ul>
Power	<ul style="list-style-type: none"> <li>3.7v / 900 mAh Li-ion battery</li> <li>Standby Time: 30 hrs</li> <li>Talking Time: 200 mins</li> </ul>
Contact pins	<ul style="list-style-type: none"> <li>3 contact pins for charging and auto-pairing</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)</li> </ul>
Base	
Power	<ul style="list-style-type: none"> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>DC jack x 1, USB type A x 2,</li> </ul>
Contact pins	<ul style="list-style-type: none"> <li>2 contact pins for charging</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g</li> <li>Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included)</li> </ul>

### 3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN300328 EN62368-1
Safety		EN301489-1 EN50360
EMC		EN301489-17 EN50566
SAR	FCC 47 CFR § 2.1093	
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	High temperature at +60°C High temperature at +35°C

#### Models:

VX-3108-BU(S)

VX-3208-BU(S)

