

VX-3108-BU(S)

VX-3208-BU(S)

1- or 2- Line Cordless
Wi-Fi Phone



VX-3108-BU(S)



VX-3208-BU(S)

- Two USB charging ports.
- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

| | Keys | 3208 | 3108 |
|---------------------|--|---|---|
| | <ul style="list-style-type: none"> Dial keys Line keys Function keys | (0~9, *, #) Line1, Line2, END Info, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys | (0~9, *, #) Line, END Info, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys |
| Phone Features | <ul style="list-style-type: none"> Up to 7 on-screen scrolling guest service icons Call Hold and resume (3208 only) Red color message waiting indicator for ringing and message waiting | | <ul style="list-style-type: none"> 3 fixed hard keys Mute and unmute (3108 only) Handset and Ringer volume control |
| Display Contents | <ul style="list-style-type: none"> Main logo Battery status, charging status Customizable vivid color display scheme Service dial list/icons | | <ul style="list-style-type: none"> Firmware Version Line status Wi-Fi signal |
| Easy Administration | <ul style="list-style-type: none"> Firmware upgrade via Wi-Fi | | <ul style="list-style-type: none"> Provisioning via Wi-Fi |
| Codec | <ul style="list-style-type: none"> G.711 (a-law, μ-law) | | |
| Network Protocols | <ul style="list-style-type: none"> DHCP | | |
| SIP | <ul style="list-style-type: none"> SIP V2 (RFC3261) | | |
| Security | <ul style="list-style-type: none"> MD5 for SIP authentication (RFC 2069/ RDC2617) | | |
| DTMF | <ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) | | |
| Tones | <ul style="list-style-type: none"> Ring back tone (local) | | |
| Wi-Fi standard | <ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n | | |
| Wi-Fi Encryption | <ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK | | |

2. Hardware Specifications

Handset

| | |
|-----------------|--|
| Display | <ul style="list-style-type: none"> 2.0" TFT color display |
| LED Indications | <ul style="list-style-type: none"> Message waiting indicator and keypad backlight |
| Power | <ul style="list-style-type: none"> 3.7v / 900mAh Li-ion battery Standby Time: 30 hrs Talking Time: 200 mins |
| Contact pins | <ul style="list-style-type: none"> 3 contact pins for charging |
| Size and Weight | <ul style="list-style-type: none"> Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included) |

Base

| | |
|-----------------|--|
| Power | <ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A |
| Jacks | <ul style="list-style-type: none"> DC jack x 1, USB type A x 2, |
| Contact pins | <ul style="list-style-type: none"> 3 contact pins for charging |
| Size and Weight | <ul style="list-style-type: none"> Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included) |

3. Regulatory

| | USA | EU |
|-------------|---|--|
| EMI | FCC Part 15B FCC Part 15C | |
| Safety EMC | | EN300328 EN62368-1 EN30148 9-1 EN301489-17 |
| SAR RoHS | FCC 47 CFR § 2.1093 Comply with directive 2011/65/EU | EN50360 EN50566 |
| Temperature | <ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at +5°C | <ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C |

Models:

VX-3108-BU(S)

VX-3208-BU(S)

