

VX-3108-BU(S)

VX-3208-BU(S)

DCS 1- or 2- Line
Cordless Wi-Fi Phone



VX-3108-BU(S)



VX-3208-BU(S)

- Two USB charging ports.
- Message waiting indicator.
- Vivid color display scheme.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	3208	3108
	<ul style="list-style-type: none"> Dial keys Line keys Function keys 	(0~9, *, #) Line1, Line2, END Info, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys	(0~9, *, #) Line, END Info, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
Display Contents	<ul style="list-style-type: none"> Up to 7 on-screen scrolling guest service icons Call Hold and resume (3208 only) Red color message waiting indicator for ringing and message waiting 		<ul style="list-style-type: none"> 3 fixed hard keys Mute and unmute (3108 only) Handset and Ringer volume control
Phone Features	<ul style="list-style-type: none"> Main logo Battery status, charging status Customizable vivid color display scheme Service dial list/icons 		<ul style="list-style-type: none"> Firmware Version Line status Wi-Fi signal
<p>* To activate voice messaging within DCS, DCS DESKTOP software is required and available for purchase separately.</p>			
Easy Administration	<ul style="list-style-type: none"> Firmware upgrade via Wi-Fi 		<ul style="list-style-type: none"> Provisioning via Wi-Fi
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law) 		
Network Protocols	<ul style="list-style-type: none"> DHCP 		
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 		
Security	<ul style="list-style-type: none"> MD5 for SIP authentication (RFC 2069/ RDC2617) 		
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 		
Tones	<ul style="list-style-type: none"> Ring back tone (local) 		
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n 		
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK 		

2. Hardware Specifications

Handset

Display	<ul style="list-style-type: none"> 2.0" TFT color display
LED Indications	<ul style="list-style-type: none"> Message waiting indicator and keypad backlight
Power	<ul style="list-style-type: none"> 3.7v / 900mAh Li-ion battery Standby Time: 30 hrs Talking Time: 200 mins
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging
Size and Weight	<ul style="list-style-type: none"> Dimensions:190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)

Base

Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	<ul style="list-style-type: none"> DC jack x 1, USB type A x 2,
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging
Size and Weight	<ul style="list-style-type: none"> Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (handset included)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN300328 EN62368-1
Safety		EN301489-1 EN50360
EMC		EN301489-1 EN50566
SAR	FCC 47 CFR § 2.1093	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Models:

VX-3108-BU(S)

VX-3208-BU(S)

