

VX-3108-XBU(A)

VX-3208-XBU(A)

1- or 2- Line Cordless
Wi-Fi Analog Master Phone



VX-3108-XBU(A)



VX-3208-XBU(A)

- Two USB charging ports.
- Message waiting indicator.
- Vivid color display scheme.
- Host up to 4 AEi Wi-Fi handsets.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



1. Features

Handset

	3208	3108
Keys	- Dial keys (0~9, *, #) - Line keys Line1, Line2, END - Hard keys EMERGENCY, GUEST SERVICES, MESSAGE - Function keys Info, VOLUME +/-, HOLD, and 3 soft keys	(0~9, *, #) - Line, END - EMERGENCY, GUEST SERVICES, MESSAGE - Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features	- Up to 7 on-screen scrolling guest service icons - Call hold and resume (3208 only) - Red color message waiting indicator for ringing and message waiting	3 programmable hard keys - Mute and unmute (3108 only) - Handset and ringer volume control
Display Contents	- Main logo - Battery status, charging status - Customizable vivid color display scheme - Service dial list/icons	- Firmware version - Line status - Wi-Fi signal
Tones	Ring back tone (local), Busy tone, Dial tone	

Connectivity

Standard	2.4GHz, IEEE 802.11 b/g/n
Encryption	WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK

Battery Backup

	3208-XBU-BB(A)	3108-XBU-BB(A)	3208-XBU(A)	3108-XBU(A)
Battery Backup	Y	Y	N	N
USB Charger	Y*	Y*	Y*	Y*

*USB chargers will stop charging while power failure

2. Hardware Specifications

Handset

Display	• 2.0"TFT color display
LED Indications	• Message waiting indicator and keypad backlight
Power	• 3.7v / 900mAh Li-ion battery
	• Standby Time: 30hrs
	• Talking Time: 200mins
Contact pins	• 3 contact pins for charging and auto-pairing
Size and Weight	• Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)

Base

Key	• Find handset key to quick locate all handsets
Power	• AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (5V / 1A for USB charging)
	• Optional battery backup while power failure
Jacks	• RJ14 PSTN jack x 1, DC jack x 1, USB type A x 2, Reset x 1
Contact pins	• 3 contact pins for charging and auto-pairing
Line cord	• 6 feet x 1
Battery backup	• Power failure backup battery 3.7v / 900mAh Li-ion (Optional)
	• Charging time: 5hrs
	• Supply standby time: 5hrs
	• Supply talking time: 3hrs
	• Power failure backup battery does not supply power to USB jacks
Size and weight	• Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g (Base only)
	• Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g (Handset and base)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 55032 EN 300328 EN 62368-1
Safety		EN 301489-1
EMC		EN 50360
SAR	FCC 47 CFR § 2.1093	EN 301489-17
PSTN	TIA/EIA 968-B compliant	EN 50566
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

VX-3108-XBU(A)

VX-3208-XBU(A)

VX-3108-XBU-BB(A)

VX-3208-XBU-BB(A)

