

SLN-1100/SLN-9100

1 or 2 Lines
SIP Phone

SLN-1200/SLN-9200



- 1 or 2 lines SIP phone.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	1200/9200	1100/9100
		(0~9, *, #)	(0~9, *, #)
		Line1, Line2 with LED, End	N/A
		Hold, Redial, Volume up/down	Volume up/down,
Phone Features		One or Two Lines	Handset and ringer volume control
		Red color message waiting indicator for ringing and message waiting	Redial last call(1200/9200)
			Call Hold and resume(1200/9200)
Easy Administration		Web GUI.	Firmware upgrade via web.
		Auto provisioning	
Codec		G.711 (a-law, μ -law)	
Network Protocol		HTTP server	Static IP, DHCP Client
		ToS / VLAN IEEE 802.1 p/q	
SIP		SIP V2 (RFC3261)	
Security		Web login authentication for web setup	MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF		In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality		CNG: Comfortable noise generator	
		Echo canceller: LEC / AEC	
		Jitter buffer/PLC	
Tones		Ring back tone (local), Busy tone, Dial tone	

2. Hardware Specifications

LED Indications	Line keys and Message waiting indicator
Power	PoE: IEEE 802.3af compliant AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	9 feet x 1
Size and Weight	Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	Storage: Low temperature at -10°C Operating Low temperature at +5°C	High temperature at +60°C High temperature at +35°C

Model:

SLN-1100

SLN-1200

SLN-9100

SLN-9200

