

VM-3108-SX(S)

1 or 2 Lines Coded

VM-3208-SX(S)

SIP Wi-Fi Master Phone



- Corded SIP Wi-Fi Master phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Host up to 4 AEi Wi-Fi handsets.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Keys	3208	3108
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with red color LED</li> <li>Function keys REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>NA</li> <li>REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>8 customizable service dials</li> <li>Call Hold and resume(3208 only)</li> <li>Handset, speaker, and ringer volume control</li> <li>Red color message key with indicator</li> <li>Host up to 4 Wi-Fi range extenders</li> </ul>	<ul style="list-style-type: none"> <li>Full duplex speaker phone</li> <li>Mute and unmute(3108 only)</li> <li>Redial last call</li> <li>Ringing indicator</li> <li>Host up to 4 VX Wi-Fi handsets</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Talking time</li> <li>IP Address</li> <li>MAC Address</li> <li>Date and time</li> </ul>	<ul style="list-style-type: none"> <li>SIP Register Status</li> <li>Firmware Version</li> <li>Failed Network link Warning</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP</li> <li>Firmware upgrade via TFTP</li> </ul>	
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC 2069/ RFC2617)</li> </ul>	<ul style="list-style-type: none"> <li>HTTPS</li> <li>TLS 1.2</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	
Wi-Fi standard	<ul style="list-style-type: none"> <li>2.4GHz, IEEE 802.11 b/g/n</li> </ul>	
Wi-Fi Encryption	<ul style="list-style-type: none"> <li>WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK</li> </ul>	

## 2. Hardware Specifications

Display	• Dot matrix LCM 16 x 2 with backlight
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	• PoE : IEEE 802.3af compliant • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)
Jacks	• RJ45 10/100 Mbs: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	• 9 feet x 1
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 630g

## 3. Regulatory

	USA	EU	
EMI	FCC Part 15B FCC Part 15C	EN55032 EN300328	EN55035
Safety		EN62386-1	
EMC		EN301489-1	EN301489-17
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	• Storage: Low temperature at -10°C • Operating Low temperature at +5°C	High temperature at +60°C	High temperature at +35°C

**Model:**

VM-3108-SX(S) [VM-3108-SX-01(S)]

VM-3208-SX(S) [VM-3208-SX-01(S)]

