

SKD-9110-S

DCS 1- or 2- Lines  
SIP Phone

SKD-9210-S



**SKD-9110-S**



**SKD-9210-S**

- Desk or wall-mountable.
- Full duplex speakerphone.
- Message waiting indicator.
- Up to 10 customizable service dials.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	9110-S	9210-S
Dialing keys		(0~9, *, #)
Line keys	N/A	Line1, Line2
Function keys	HOLD, REDIAL, MUTE, SPEAKER, Volume up/down, 10 Service dial keys	
Phone Features	<ul style="list-style-type: none"> <li>Up to 10 programmable service dial keys</li> <li>Handset and ringer volume control</li> <li>Call Hold and resume</li> <li>Speaker volume control</li> <li>Full duplex speaker phone</li> <li><i>*Voice message is disable in a DCS network</i></li> </ul>	<ul style="list-style-type: none"> <li>Desk or wall-mountable</li> <li>Redial last call</li> <li>Mute and unmute</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP, SFTP</li> </ul>	<ul style="list-style-type: none"> <li>Firmware upgrading via TFTP, SFTP</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC 2069/ RFC2617)</li> </ul>	<ul style="list-style-type: none"> <li>HTTPS</li> <li>TLS 1.2</li> <li>S RTP</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>LINE keys (9210-S), MUTE, SPEAKER, and Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE: IEEE 802.3af compliant</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>9 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

### Model:

SKD-9110-S

SKD-9210-S

