

VM-9200-SLT(S) | DCS Admin Phone



- DCS Admin phone.
- Magnetic hook switch.
- 4.3-inch touch screen.
- Full duplex speakerphone.
- Message waiting key with indicator.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2 with red color LED • Function keys LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE 	
Phone Features	<ul style="list-style-type: none"> • 4.3" TFT color touch screen • Call hold and resume • Red color message key with indicator • Programmable voice message key with indicator • Call gateway 	<ul style="list-style-type: none"> • Speaker and ringer volume control • Full duplex speaker phone • Redial last call • Ringing indicator
Display Contents	<ul style="list-style-type: none"> • Phone online/offline status in DCS network • Date and time • Firmware version • IP address 	<ul style="list-style-type: none"> • MAC address • Talking time • SIP register status • Failed network link warning
Easy Administration	<ul style="list-style-type: none"> • Web GUI • Auto provisioning via TFTP 	<ul style="list-style-type: none"> • Firmware upgrade via TFTP
Codec	<ul style="list-style-type: none"> • G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> • HTTP server • ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> • Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> • Web login authentication for web setup • MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> • HTTPS • TLS 1.2
DTMF	<ul style="list-style-type: none"> • In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> • Echo canceller: LEC / AEC • CNG: comfortable noise generator 	<ul style="list-style-type: none"> • Jitter buffer/PLC
Tones	<ul style="list-style-type: none"> • Ring back tone (local), Busy tone, Dial tone 	

2. Hardware Specifications

Display	<ul style="list-style-type: none"> Type: 4.3" resistive touch WQVGA color TFT with backlight Resolution: 272 x 480 pixels Display size W x H: 55.5mm x 96.7mm
LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> PoE: IEEE 802.3af compliant AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)
Jacks	<ul style="list-style-type: none"> RJ45 10/100Mbps: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 9 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 680g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	Storage: Low temperature at -10°C	High temperature at +60°C
	Operating: Low temperature at +5°C	High temperature at +35°C

Model:

VM-9200-SLT-9901(S)

