

VM-9100-SLT(S)

1- or 2- Lines  
Touch Screen  
SIP Phone

VM-9200-SLT(S)



**VM-9100-SLT(S)**



**VM-9200-SLT(S)**

- Magnetic hook switch.
- 4.3-inch touch screen.
- Multi language support
- Full duplex speakerphone.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	9200	9100
Keys	<ul style="list-style-type: none"> <li>● Dial keys (0~9, *, #)</li> <li>● Line keys Line1, Line2 with red color LED</li> <li>● Function keys LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE</li> </ul>	<ul style="list-style-type: none"> <li>● (0~9, *, #)</li> <li>● N/A</li> <li>● LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>● 4.3" TFT color touch screen</li> <li>● Customizable service menu</li> <li>● Call Hold and resume (9200 only)</li> <li>● Red color message key with indicator</li> <li>● Redial last call</li> </ul>	<ul style="list-style-type: none"> <li>● Speaker and ringer volume control</li> <li>● Full duplex speaker phone</li> <li>● Mute and unmute (9100 only)</li> <li>● Multiple languages support</li> <li>● Ringing indicator</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>● Hotel logo</li> <li>● Service menu</li> <li>● Language menu</li> <li>● Date and time</li> <li>● Firmware version</li> </ul>	<ul style="list-style-type: none"> <li>● Talking time</li> <li>● IP address</li> <li>● MAC address</li> <li>● SIP register status</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>● Web GUI</li> <li>● Auto provisioning via TFTP</li> </ul>	<ul style="list-style-type: none"> <li>● Failed network link warning</li> <li>● Firmware upgrade via TFTP</li> </ul>
Codec	<ul style="list-style-type: none"> <li>● G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>● HTTP server</li> <li>● ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>● Static IP, DHCP Client</li> </ul>
SIP	<ul style="list-style-type: none"> <li>● SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>● Web login authentication for web setup</li> <li>● MD5 for SIP authentication (RFC 2069/ RFC2617)</li> </ul>	<ul style="list-style-type: none"> <li>● HTTPS</li> <li>● TLS 1.2</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>● In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>● Echo canceller: LEC / AEC</li> <li>● CNG: Comfortable noise generator</li> </ul>	<ul style="list-style-type: none"> <li>● Jitter buffer/PLC</li> </ul>
Tones	<ul style="list-style-type: none"> <li>● Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

Display	<ul style="list-style-type: none"> <li>Type 4.3" resistive touch WQVGA color TFT with backlight</li> <li>Resolution 272 x 480 pixels</li> <li>Display size W x H 55.5mm x 96.7mm</li> </ul>
LED Indications	<ul style="list-style-type: none"> <li>Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE: IEEE 802.3af compliant</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>9 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 680g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

**Model:**

VM-9100-SLT-9901(S)

VM-9200-SLT-9901(S)

