

VM-9108-SM(A)

VM-9208-SM(A)

1- or 2- Line Coded
Analog DECT Master Phone



VM-8108-SMK(A)



VM-8208-SMK(A)

- Magnetic hook switch.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	9208	9108
	- Dial keys - Line keys - Function keys	(0~9, *, #) Line1, Line2 with red color LED REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys	(0~9, *, #) N/A REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	- Up to 8 programmable guest service keys - Programmable voice message key with indicator - Call hold and resume (9208) - Speaker and ringer volume control		- Redial last call - Ringing indicator - Mute and unmute (9108) - Full duplex speaker phone
DECT Standard	- DECT / CAT iq 2.0 compatible - Radio Frequency Range : 1880~1930 MHz - EU: 1881.792(ch0)~1897.344(ch9) 10 channels - US: 1921.536(ch0)~1928.448(ch4) 5 channels - JP: 1895.616(ch0)~1902.528(ch4) 5 channels		- Channel Space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 17 dBm

2. Hardware Specifications

LED Indications	Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	RJ14(RJ11) PSTN jack x 1, DC jack x 1, RJ9 Handset jack x 1
Line cord	6 feet x 1
Size and Weight	Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 610g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	- Storage: Low temperature at -10°C - Operating: Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Model:

VM-9108-SM(A)
 VM-9208-SM(A)
 VM-9108-SM-N1(A)
 VM-9208-SM-N1(A)

