

VM-9108-S(S)

VM-9208-S(S)

1- or 2- Line
SIP Phone



VX-9108-S(S)



VM-9208-S(S)

- Magnetic hook switch.
- Full duplex speakerphone.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	9208	9108
		- Dial keys (0~9, *, #) - Line keys Line1, Line2 with red color LED - Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys	(0~9, *, #) - NA - REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features		- Up to 8 programmable guest service keys - Programmable voice message key with indicator - Call hold and resume(9208) - Handset, speaker and ringer volume control	- Full duplex speaker phone - Ringing indicator - Mute and unmute(9108) - Redial last call
Display Contents		- Talking time - IP address - MAC address - Date and time	- SIP register status - Firmware version - Failed network link warning
Easy Administration		- Web GUI - Auto provisioning via TFTP	Firmware upgrade via TFTP
Codec		G.711 (a-law, μ-law)	
Network Protocol		- HTTP server - ToS / VLAN IEEE 802.1 p/q	Static IP, DHCP Client
SIP		SIP V2 (RFC3261)	
Security		- Web login authentication for web setup - MD5 for SIP authentication (RFC 2069/ RFC2617)	- HTTPS - TLS 1.2
DTMF		In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality		- CNG: comfortable noise generator - Echo canceller: LEC / AEC - Jitter buffer/PLC	
Tones		Ring back tone (local), busy tone, dial tone	

2. Hardware Specifications

Display	• Dot matrix LCM 16 x 2 with backlight
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	• PoE: IEEE 802.3af compliant • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)
Jacks	• RJ45 10/100Mbps: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	• 6 feet x 1
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 630g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

VM-9108-S(S)

VM-9208-S(S)

