

SLN-3110-W

1- or 2- Lines SIP Phone  
- Wireless Connect

SLN-3210-W



**SLN-3110-W**



**SLN-3210-W**

- Connect wirelessly to access point
- Up to 10 customizable service dials.
- Faceplate with customizable hotel logo.
- Message waiting indicator.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	3110	3210
Dialing keys	(0~9, *, #)	(0~9, *, #)
Line keys	N/A	Line1, Line2
Function keys	HOLD, REDIAL, Volume up/down, 10 guest service keys	
Phone Features	<ul style="list-style-type: none"> <li>Connect directly to access point</li> <li>Up to 10 programmable guest service keys</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>	<ul style="list-style-type: none"> <li>Handset and ringer volume control</li> <li>Redial last call</li> <li>Call Hold and resume</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Auto provisioning via TFTP</li> <li>Firmware upgrade via TFTP</li> </ul>	<ul style="list-style-type: none"> <li>Web GUI.</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, μ-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>TLS 1.2</li> </ul>	<ul style="list-style-type: none"> <li>MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	
Wi-Fi standard	<ul style="list-style-type: none"> <li>2.4GHz, IEEE 802.11 b/g/n</li> </ul>	
Wi-Fi Encryption	<ul style="list-style-type: none"> <li>WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK</li> </ul>	

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Line keys (3210), Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 300328 EN 62368-1 EN 301489-1
Safety EMC		EN 301489-17
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating: Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul>

### Model:

SLN-3110-W

SLN-3210-W

