

VM-3108-SX(A)

VM-3208-SX(A)

1- or 2- Line Coded
Analog Wi-Fi Master Phone



VM-3108-SX(A)



VM-3208-SX(A)

- Magnetic hook switch.
- Full duplex speakerphone.
- Host up to 4 AEi Wi-Fi handsets.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	3208	3108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys 	<ul style="list-style-type: none"> (0~9, *, #) NA REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	<ul style="list-style-type: none"> Up to 8 programmable guest service keys Programmable voice message key with indicator Call hold and resume (3208 only) Handset, speaker and ringer volume control Host up to 4 Wi-Fi range extenders 	<ul style="list-style-type: none"> Full duplex speaker phone Redial last call Mute and unmute (3108 only) Ringing indicator Host up to 4 AEi Wi-Fi handsets
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n 	
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK 	

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	<ul style="list-style-type: none"> RJ14 PSTN jack x 1, DC jack x 1, RJ9 Handset jack x 1
Line cord	<ul style="list-style-type: none"> 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 650g

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 55032 EN 300328
Safety		EN 62386-1
EMC		EN 301489-1
SAR	FCC 47 CFR § 2.1093	EN 50360 EN 50566
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

VM-3108-SX(A)

VM-3208-SX(A)

