

VM-3108-SXK(A)

VM-3208-SXK(A)

1- or 2- Line Cordless
Analog Wi-Fi Master Phone



VM-3108-SXK(A)



VM-3208-SXK(A)

- Magnetic hook switch.
- Full duplex speakerphone.
- Host up to 4 AEi Wi-Fi handsets.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	3208	3108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Hard keys EMERGENCY, GUEST SERVICES, MESSAGE Function keys Info, VOLUME +/-, HOLD, and 3 soft keys 	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line, END EMERGENCY, GUEST SERVICES, MESSAGE Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features	<ul style="list-style-type: none"> Up to 7 on-screen scrolling guest service icons Call hold and resume (3208 only) Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> 3 programmable hard keys Mute and unmute (3108 only) Handset and ringer volume control
Display Contents	<ul style="list-style-type: none"> Main logo Battery status, charging status Customizable vivid color display scheme Service dial list/icons 	<ul style="list-style-type: none"> Firmware version Line status Wi-Fi signal
Tones	<ul style="list-style-type: none"> Ring back tone (local) 	
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n 	
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK 	

Base

	3208	3108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys 	<ul style="list-style-type: none"> Dial keys (0~9, *, #) N/A REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	<ul style="list-style-type: none"> Up to 8 programmable guest service keys Programmable voice message key with indicator Call hold and resume (3208 only) Speaker and ringer volume control Host up to 4 Wi-Fi range extenders 	<ul style="list-style-type: none"> Full duplex speaker phone Redial last call Mute and unmute (3108 only) Ringing indicator Host up to 4 AEI Wi-Fi handsets
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n 	
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK 	

2. Hardware Specifications

Handset

- Display • 2.0" TFT color display
- LED Indications • Message waiting indicator and keypad backlight
- Power • 3.7v / 900mAh Li-ion battery
- Standby Time: 30 hrs
- Talking Time: 200 mins
- Contact pins • 3 contact pins for charging and auto-pairing
- Size and Weight • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

- LED Indications • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
- Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
- Jacks • RJ14 PSTN jack x 1, DC jack x 1
- Contact pins • 3 contact pins for charging and auto-pairing
- Line cord • 10 feet x 1
- Size and Weight • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 580g

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 55032 EN 300328
Safety		EN 62386-1
EMC		EN 301489-1
SAR	FCC 47 CFR § 2.1093	EN 50360
PSTN	TIA/EIA 968-B compliant	EN 301489-17
RoHS	Comply with directive 2011/65/EU	EN 50566
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

VM-3108-SXK(A)

VM-3208-SXK(A)

