

VX-3108-XBU(A)

VX-3208-XBU(A)

1- or 2- Line Cordless
Wi-Fi Analog Master Phone



VX-3108-XBU(A)



VX-3208-XBU(A)

- Two USB charging ports.
- Message waiting indicator.
- Vivid color display scheme.
- Host up to 4 AEi Wi-Fi handsets.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	3208	3108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Hard keys EMERGENCY, GUEST SERVICES, MESSAGE Function keys Info, VOLUME +/-, HOLD, and 3 soft keys 	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line, END EMERGENCY, GUEST SERVICES, MESSAGE Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features	<ul style="list-style-type: none"> Up to 7 on-screen scrolling guest service icons Call hold and resume (3208 only) Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> 3 programmable hard keys Mute and unmute (3108 only) Handset and ringer volume control
Display Contents	<ul style="list-style-type: none"> Main logo Battery status, charging status Customizable vivid color display scheme Service dial list/icons 	<ul style="list-style-type: none"> Firmware version Line status Wi-Fi signal
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	

Connectivity

Standard Encryption	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK
---------------------	---

Battery Backup

	3208-XBU-BB(A)	3108-XBU-BB(A)	3208-XBU(A)	3108-XBU(A)
Battery Backup	Y	Y	N	N
USB Charger	Y*	Y*	Y*	Y*

*USB chargers will stop charging while power failure

2. Hardware Specifications

Handset

- Display • 2.0" TFT color display
- LED Indications • Message waiting indicator and keypad backlight
- Power • 3.7v / 900mAh Li-ion battery
- Standby Time: 30hrs
- Talking Time: 200mins
- Contact pins • 3 contact pins for charging and auto-pairing
- Size and Weight • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g (battery included)

Base

- Key • Find handset key to quick locate all handsets
- Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (5V / 1A for USB charging)
- Optional battery backup while power failure
- Jacks • RJ14 PSTN jack x 1, DC jack x 1, USB type A x 2, Reset x 1
- Contact pins • 3 contact pins for charging and auto-pairing
- Line cord • 10 feet x 1
- Battery backup • Power failure backup battery 3.7v / 900mAh Li-ion (Optional)
- Charging time: 5hrs
- Supply standby time: 5hrs
- Supply talking time: 3hrs
- Power failure backup battery does not supply power to USB jacks
- Size and weight • Dimensions: 115.7mm(L) x 104.5mm(W) x 98.8mm(H), Weight: 340g (Base only)
- Dimensions: 115.7mm(L) x 104.5mm(W) x 190mm(H), Weight: 480g (Handset and base)

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 55032 EN 300328 EN 62368-1
Safety		EN 301489-1
EMC		EN 50566
SAR	FCC 47 CFR § 2.1093	
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

- VX-3108-XBU(A)
- VX-3208-XBU(A)
- VX-3108-XBU-BB(A)
- VX-3208-XBU-BB(A)

