

VM-3108-SXW(S)

1- or 2- Line
 SIP Wi-Fi Master Phone
 - Wireless Connect

VM-3208-SXW(S)



VX-3108-SXW(S)



VM-3208-SXW(S)

- Magnetic hook switch.
- Full duplex speakerphone.
- Host up to 4 AEi Wi-Fi handsets.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Connect wirelessly to hotel access point.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	3208	3108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys 	<ul style="list-style-type: none"> (0~9, *, #) NA REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	<ul style="list-style-type: none"> Connect wirelessly to hotel access point Up to 8 programmable guest service keys Programmable message key with indicator Call hold and resume (3208 only) Handset, speaker, and ringer volume control Host up to 4 AEi Wi-Fi range extenders 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute (3108 only) Redial last call Ringing indicator Host up to 4 AEi Wi-Fi handsets
Display Contents	<ul style="list-style-type: none"> Talking time IP address MAC address Date and time 	<ul style="list-style-type: none"> SIP register status Firmware version Failed network link warning
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP Firmware upgrade via TFTP 	
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> HTTP server ToS / VLAN IEEE 802.1 p/q SIP V2 (RFC3261) 	<ul style="list-style-type: none"> Static IP, DHCP Client
SIP Security	<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> HTTPS TLS 1.2
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> CNG: comfortable noise generator Echo canceller: LEC / AEC Jitter buffer/PLC 	
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
Wi-Fi standard	<ul style="list-style-type: none"> 2.4GHz, IEEE 802.11 b/g/n 	
Wi-Fi Encryption	<ul style="list-style-type: none"> WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK 	

2. Hardware Specifications

- Display • Dot matrix LCM 16 x 2 with backlight
- LED Indications • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
- Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
- Jacks • RJ9 Handset jack x 1, DC jack x 1
- Size and Weight • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 630g

3. Regulatory

	USA	EU
EMI	FCC Part 15B FCC Part 15C	EN 300328 EN 62386-1
Safety		EN 301489-1
EMC		EN 301489-17
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

VM-3108-SXW(S)

VM-3208-SXW(S)

