

Single Line SIP Emergency Phone



- AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.



1. Features

Keys	• Function keys	• Volume up/down,	
Phone Features	• Red color message waiting indicator for ringing and message waiting		• Desk or wall-mountable • Handset and ringer volume control
Easy Administration	• Web GUI.		• Firmware upgrade via web.
	• Auto provisioning		
Codec	• G.711 (a-law, μ -law)		
Network Protocol	• HTTP server		• Static IP, DHCP Client
	• ToS / VLAN IEEE 802.1 p/q		
SIP	• SIP V2 (RFC3261)		
Security	• Web login authentication for web setup		• TLS 1.2
	• MD5 for SIP authentication (RFC2069/ RFC2617)		
DTMF	• In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)		
Voice Quality	• CNG: comfortable noise generator		
	• Echo canceller: LEC / AEC		
	• Jitter buffer/PLC		
Tones	• Ring back tone (local), Busy tone, Dial tone		

2. Hardware Specifications

LED Indications	• Message waiting indicator
Power	• PoE: IEEE 802.3af compliant • AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	• RJ45 10/100Mbps: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	• 6 feet x 1
Size and Weight	• Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C • Operating: Low temperature at +5°C	High temperature at +60°C High temperature at +35°C

Model:
SKD-1100 Emergency Phone

